

## DUAL VIEW TECHNOLOGY AND A HEAVY DUTY DESIGN FOR PALLET AND AIR CARGO X-RAY SCREENING.

ADVANCED CARGO SCREENING

DUAL VIEW TECHNOLOGY

BREAK BULK AND PALLET CARGO

DETECTION OF EXPLOSIVES AND NARCOTICS ALERT

### STANDARD FEATURES

- Multi Energy Imaging (4 Color)
- View Previous/Next Bag
- Image Archive
- Configurable Image Processing Keys
- Baggage Counter
- Date / Time Display
- Search Indicator
- UPS (Uninterrupted Power Supply)
- Multi Language Support
- Flat Panel Monitor

### STANDARD IMAGE PROCESSING FUNCTIONS

- Crystal Clear™
- Black and White
- Organic / Inorganic Stripping
- Inverse Video
- High Penetration
- Pseudo Color
- Low Penetration
- Variable Edge Enhancement
- Variable Color Stripping
- Variable Gamma
- Variable Density
- Dynamic Continuous Zoom & Panning
- Fixed Zoom (64x)

sales@rapiscansystems.com  
www.rapiscansystems.com



Tunnel Opening (width x height):  
1,537 x 1,650 mm (60.5 x 65.0 in)

THE RAPISCAN 632DV IS AN ADVANCED CARGO AND LARGE PARCEL SYSTEM DESIGNED FOR INSPECTION OF PALLET AND BREAK BULK CARGO SCREENING. THE RAPISCAN 632DV TUNNEL OPENING OF 1,500 MM X 1650 MM, DETECTION OF EXPLOSIVES AND NARCOTICS ALERT, DUAL VIEW TECHNOLOGY, AND SUPERIOR IMAGE QUALITY ALLOWS HIGH THROUGHPUT OF SCREENED OBJECTS.

The Rapiscan 632DV has been approved and included on the U.S. TSA Air Cargo Screening Technology List (ACSTL) and the Transport Canada (TC) Air Cargo Security Program (ACS).

### DETECTION OF EXPLOSIVES AND NARCOTICS ALERT

Target™ and NARCScan™ are designed to assist operators in the detection of a range of explosives and narcotics respectively in real time during the scanning process by marking a potential threat on the X-ray image. Rapiscan detection algorithms are based on regulatory material analysis techniques.

### REGULATORY COMPLIANCE

Rapiscan 632DV performance is in full compliance with the European Union regulations (EC) No. 300/2008, (EU) No. 2015/1998 and Commissions Decision C (2015)8005 for aviation security.

### EASE OF USE PROVIDING HIGHEST THROUGHPUT

With over 13 image processing tools and detection alert algorithm functions, the feature rich software allows the operator to more easily and accurately search for contraband.

### DUAL VIEW ADVANCED TECHNOLOGY

As mandated by US and EU regulators, the 632DV utilizes a dual-view technology which produces two simultaneous images (vertical and horizontal views) of the scanned object. It provides a more complete image, thereby reducing the need for repositioning and rescanning and enabling rapid, accurate and comprehensive threat detection.


### DARC ALARM

Rapiscan's proprietary detection algorithm that detects areas of high density while screening air cargo. Rapiscan collaborated closely with the U.K. Department for Transport to create DARC alarm and jointly executed the necessary test trials to verify the effectiveness of the DARC Alarm algorithm.



# RAPISCAN 632DV

**Rapiscan**<sup>®</sup>  
systems  
An OSI Systems Company



## PHYSICAL SPECIFICATIONS

Dimensions:	Length: 7,788 mm (306.6 in.) Width: 2,816 mm (110.9 in.) Height: 3,331 mm (131.1 in.)
Tunnel Size:	1,537 mm (60.5 in.) X 1,650 mm (65.0 in.)
Conveyor Speed:	0.20 m/sec (39.4 ft./min)
Conveyor Load (Max):	3,000 Kg (6,614 lbs) evenly distributed at 230 V 1,500 Kg (3,307 lbs) evenly distributed at 115 V
Conveyor Height:	345 mm (13.6 in.)
Weight (Approx.):	Net: 4,823 Kg (10,633 lbs)
System Power:	115/230 VAC ±10%, 60/50Hz

## X-RAY GENERATOR AND IMAGE PERFORMANCE<sup>1</sup>

Steel Penetration:	50 mm typical; 45 mm standard
Wire Resolution:	40 AWG typical; 38 AWG standard
Cooling:	Sealed oil bath with forced air
Anode Voltage:	Operating at 200kV
Tube Current:	1.0 mA
Orientation:	Vertically Downward and Horizontal

## OPERATING ENVIRONMENT

Storage Temperature:	-20°C to 50°C
Operating Temperature:	0°C to 40°C
Relative Humidity:	5 to 95% non-condensing

## PROTECTION CLASS

System:	IP20
Operator Control Panel:	IP43 <sup>2</sup>

## REGULATORY

- TSA Air Cargo Screening Technology List (ACSTL) Qualified
- Transport Canada (TC) Air Cargo Qualified
- Regulation (EC) No. 300/2008 Compliant
- Regulation (EU) No. 2015/1998 Compliant
- EU Commissions Decision (EU) C(2015)8005 Compliant
- French Civil Aviation Authority (STAC) Certified

## AMERICAS, CARIBBEAN

2805 Columbia Street  
Torrance,  
California  
90503  
UNITED STATES of AMERICA

Tel: +1 310-978-1457  
Fax: +1 310-349-2491

## EUROPE, MIDDLE EAST, AFRICA

X-Ray House  
Bonehurst Road  
Salfords  
Surrey RH1 5GG  
UNITED KINGDOM

Tel: +44 (0) 870-7774301  
Fax: +44 (0) 870-7774302

## ASIA

240 Macpherson Road  
#07-01 Pines Industrial Building  
Singapore  
348574  
SINGAPORE

Tel: +65-6846-3511  
Fax: +65-6743-9915

## OPTIONS AND ACCESSORIES

- Explosive Detection Alert (Target™)
- Narcotics Detection Alert (NARCScan™)
- Density Threshold Alert (DTA)
- Threat Image Projection (TIP)
- Threat Image Projection Network (TIPNet)
- Remote Image Archive Review (NETView™)
- Network X-ray management automation and link system (NEXLink™)
- Multi-System Network Display Station (NDS)
- Automatic Image Archiving
- Enhanced Image Archiving
- Operator Training Program (OTP)
- Manual Scan
- Foot Mat
- Optical Operator Presence Sensor
- SmartCard Login
- Power Conditioner
- Conveyor Accessories
- Universal Printer Support

<sup>1</sup> Stated performance as measured by Rapiscan Imaging Validation Test Kit.

Stated dual view performance as measured in primary view.

<sup>2</sup> With optional replaceable cover.

With continual development of our products Rapiscan Systems reserves the right to amend specifications without notice. Product pictures are for general reference. Please note that due to US laws and regulations, not all Rapiscan products are available for sale in all countries without restriction. Please contact your Rapiscan Systems sales representative for more information.



Rapiscan Systems is ISO 9001:2008 and ISO 14001:2004 + Cor. 1:2009 Certified

sales@rapiscansystems.com  
www.rapiscansystems.com